

2-Way Ball Valves

Inlet Female Swivel	(2) Outlet Male	Aluminum Part #
1-1/2" NST (NH)	1-1/2" NST (NH)	FMBV15F15F
1-1/2" NPSH	1-1/2" NPSH	FMBV15S15S
2-1/2" NST (NH)	1-1/2" NST (NH)	FMBV25F15F
	2-1/2" NST (NH)	FMBV25F25F
4" NST (NH)	2-1/2" NST (NH)	FMBV40F25F
4-1/2" NST (NH)	2-1/2" NST (NH)	FMBV45F25F



Storz Inlet with 2 Outlets 2-Way Ball Valves

Application

- This valve will feed two smaller attack lines from one large diameter supply line. The 2½" outlet is a gated ball valve resulting in a safe controlled flow of water.

Features

- Available with a Storz or threaded combinations.
- It can be used to distribute water in the opposite direction
- Water way: inlet side - 4-1/2" maximum, 2 outlets - 2-1/2" maximum
- Finish hardcoat anodized throughout - minimum thickness 0.001"

Material

- High strength aluminum alloy, 356-T6

Specification

- Up to **280 PSI** working pressure without relief valve at 70°F (21°C)



Inlet Storz	(2) Outlet Storz	Part #	Length	Width	Height
2-1/2"	2-1/2"	SBV2525	9"	8"	7"
3"	2-1/2"	SBV325	9"	8-1/2"	7"
4"	2-1/2"	SBV425	12"	9-3/4"	9"
5"	2-1/2"	SBV525	12-1/2"	12"	9"
6"	2-1/2"	SBV625	13"	12"	9"

Plain Wyes with Pin Lugs

Features

- Divides one stream into two
- Other configurations are available, contact Dixon® for additional information

Inlet Female	(2) Outlets Male	Cast Brass Part #
1-1/2" NST (NH)	1-1/2" NST (NH)	PW15F15F
1-1/2" NPSH	1-1/2" NPSH	PW15S15S
2-1/2" NST (NH)	1-1/2" NST (NH)	PW25F15F
	2-1/2" NST (NH)	PW25F25F



NOTE: no rebuild kits