

### Straight GHT Valve

**Specifications**

- Maximum temperature: **160°F (71°C)** (hot water)
- Recommended usage: **100°F (38°C)**
- Working pressure: **60 PSI**

**Powder-coated Zinc Part #**

GHV



### GHT Ball Valve

**Specifications**

- Maximum temperature: **140°F (60°C)** (hot water)
- Working pressure: **100 PSI**
- Reduced port

**Description**

**Forged Brass Part #**

3/4" female x 3/4" male GH

500GHV



### GHT Twin Valve

**Specifications**

- Maximum temperature: **160°F (71°C)** (hot water)
- Recommended usage: **100°F (38°C)**
- Working pressure: **60 PSI**

**Powder-coated Zinc Part #**

GHYV



### Garden Hose Y Valve

**Feature**

- Double Y valve, swivel inlet - with Higbee cut threads (capped) to prevent cross threading

**Specifications**

- Maximum temperature: **140°F (60°C)** (hot water)
- Working pressure: **100 PSI**

**Description**

**Forged Brass Part #**

3/4" female x double 3/4" male GH

500GHY



### Garden Hose Y Coupler

**Specifications**

- Maximum working pressure: **100 PSI**
- Maximum temperature: **140°F (60°C)**

**Description**

**Nickel-plated Forged Brass Part #**

3/4" female x double 3/4" male GH

500YCF



### GHT Y

**Feature**

- Includes one end cap

**Specifications**

- Maximum temperature: **160°F (71°C)** (hot water)
- Recommended usage: **100°F (38°C)**
- Working pressure: **60 PSI**

**Powder-coated Zinc Part #**

GHY

